



This white non-woven fabric consisting of cellulose and polyester has been especially developed for automatic blanket cleaning within printpresses. Features as: low lint, balanced absorptive capacity, high tear-resistance and low lint secure excellent cleaning under wet conditions.

MULTISORB



TECHNICAL DATA:

<i>Fabric weight</i>	73 g/m²	<i>stand.deviation</i>	2,4
<i>Avg. Thickness</i>	260 micron	<i>stand.deviation</i>	16
<i>Permeability 196 Pa</i>	660 (L/M²/S)	<i>stand.deviation</i>	132
<i>Tensile strength MD</i>	2750 N/M	<i>stand.deviation</i>	396
<i>Tensile strength CD</i>	860 N/M	<i>stand.deviation</i>	124
<i>Elongation MD</i>	17 %		
<i>Elongation CD</i>	32 %		
<i>Trapezium Tear MD</i>	1590 cN		
<i>Trapezium Tear CD</i>	2260 cN		
<i>Ratio Wet/ Dry</i>	50 %		
<i>Absorbive Capacity</i>	500 %		
<i>Water Drop test</i>	1 second		

The facts stated and the recommendations and suggestions herein are based upon experiment and information believed to be reliable. No guarantee is made of their accuracy however, and DIMPLE assumes no liability for product failure other than to supply replacement material for DIMPLE shown to be defective when delivered. Except as stated above, there are no warranties expressed or implied on merchantability fitness for use, or otherwise. DIMPLE shall not be liable for special, incidental and consequential damages. No statement containing herein shall be construed as an inducement to infringe existing patents or as an endorsement of products of specific manufacture.